

FEATURES

- Ideal for Embedded Applications directly on your own boards
- No multiplexing, 8 Independent channels
- Input Range $\pm 100V$
- 3 KVRms Isolation Input, Power and SPi Link
- 2 kVRms Channel-to-Channel Isolation
- 250 VRms Signal Overage Protection
- Highly stable Apix technology A/D Conversion
- 120 db Common Mode Rejection
- 90 db Normal Mode Rejection 50/60 HZ
- 50 to 1000 Conversions/Sec for all 8 channels converting synchronously
- +5 Volt Supply, 250 mADC
- -40 to 85 °C Operating Temperature Range

DESCRIPTION

The Daqpak SPi Series Voltage Input Modules feature 8 independent channels and an SPi interface. They are fully isolated with 3 KVRms between Input, Power, SPi serial link and 2 KVRms Channel-to-Channel.

These are extremely compact and are ideal for embedded applications directly on your own boards. They combine Signal Conditioning, robust Isolation, and highly stable A/D conversion technologies per channel.

All 8 channels convert synchronously. The sampling rate of 60 Hz per 8 channel set is the default rate in order to take advantage of the rejection notches in the frequency response, coinciding with the power line frequency and its harmonics.

The sampling frequency can be set by the user from 50 to 1000 Hz. If higher rates are required, please contact factory.

SPECIFICATIONS

MAXIMUM RATINGS

Power Supply Voltage (Vdd)	-0.5 to 6 VDC
Analog Input	250 VRms
Storage Temperature	-55 to 125 Deg C

ANALOG INPUT

Voltage Range	$\pm 100 V$
Bandwidth	1000 Hz (-3db) Max
Input Resistance	1 MOhm
Normal Mode Rejection	90 db at 50/60 Hz

COMMON MODE

Maximum CMV	3 KVRms
Rejection	120 db at 50/60 Hz
Leakage Current	2 μA rms at 1000 VRms
	50/60 Hz per channel
Capacitance	4 pF Total per channel

DIGITAL OUTPUT

Resolution	16 Bits Serial SPi
Conversion Rate	50 to 1000 Hz

PERFORMANCE

Initial Accuracy	$\pm 0.01 \%$ of SPAN
Zero Drift	± 10 ppm per °C
Span Drift	± 20 ppm per °C

POWER REQUIREMENTS

Supply Voltage Range	5 VDC $\pm 5 \%$
Supply Current	250 mA Max
Power Consumption	1250 mW Max

ENVIRONMENTAL & MECHANICAL

Operating Temperature	-40 to 85 °C
Relative Humidity	< 95 % Non Condensing
Overall Dimensions	1.8 x 2 x 0.5 (inches) 46 x 51 x 13 (mm)